


N0210
BSP REDUCING NIPLES- DIN PROFILE
NIPLES DI RIDUZIONE BSP – PROFILO DIN

part number codice	thread F1	thread F2	L		CH		Max Pressure	
			[in]	[mm]	[in]	[mm]	[psi]	[bar]
N02100402I	1/4"-19	1/8"-28	1,22	31,0	0,75	19	5076	350
N02100602I	3/8"-19	1/8"-28	1,22	31,0	0,87	22	5076	350
N02100604I	3/8"-19	1/4"-19	1,30	33,0	0,87	22	5076	350
N02100804I	1/2"-14	1/4"-19	1,46	37,0	1,06	27	5076	350
N02100806I	1/2"-14	3/8"-19	1,50	38,0	1,06	27	5076	350
N02101008I	5/8"-14	1/2"-14	1,58	40,0	1,18	30	4351	300
N02101204I	3/4"-14	1/4"-19	1,50	38,0	1,26	32	3626	250
N02101206I	3/4"-14	3/8"-19	1,50	38,0	1,26	32	3626	250
N02101208I	3/4"-14	1/2"-14	1,69	43,0	1,26	32	3626	250
N02101210I	3/4"-14	5/8"-14	1,69	43,0	1,26	32	3626	250
N02101608I	1"-11	1/2"-14	1,85	47,0	1,62	41	2901	200
N02101612I	1"-11	3/4"-14	1,93	49,0	1,62	41	2901	200
N02102012I	1.1/4"-11	3/4"-14	2,21	53,0	1,97	50	2901	200
N02102016I	1.1/4"-11	1"-11	2,21	56,0	1,97	50	2901	200
N02102412I	1.1/2"-11	3/4"-14	2,16	55,0	2,17	55	2538	175
N02102416I	1.1/2"-11	1"-11	2,21	56,0	2,17	55	2538	175
N02102420I	1.1/2"-11	1.1/4"-11	2,32	59,0	2,17	55	2538	175
N02103216I	2"-11	1"-11	2,52	64,0	2,76	70	2176	150
N02103220I	2"-11	1.1/4"-11	2,60	66,0	2,76	70	2176	150
N02103224I	2"-11	1.1/2"-11	2,68	68,0	2,76	70	2176	150