



DOUBLE STEEL WIRE HELIX HOSE – SAE100 R4
TUBO R4 – SAE 100 – DOPPIA SPIRALE

HHOR4

Part Number Codice	hose ID		Inside Ø [mm]	Braid Ø [mm]	Outside Ø [mm]	Working Pressure		Test Pressure Bar	Burst Pressure Bar	Bend Radius mm	Weight kg/m
	[in]	[mm]				Bar	Psi				
HHOR41201T	3/4"	19,0	19,0	-	29,0	21	300	-	84	95	0,60
HHOR41601T	1"	25,4	25,4	-	35,4	17	250	-	68	125	0,70
HHOR42001T	1.1/4"	31,8	31,8	-	41,8	14	200	-	56	160	0,90
HHOR42401T	1.1/2"	38,1	38,1	-	49,0	10	140	-	40	200	1,10
HHOR43201T	2"	50,8	51,0	-	62,0	7	100	-	28	255	1,35
HHOR43801T	2.1/2"	63,0	63,5	-	76,5	5	70	-	20	315	1,90
HHOR44801T	3"	76,0	76,2	-	89,2	5	70	-	20	380	2,50
HHOR45601T	3.1/2"	90,0	89,0	-	102,0	5	70	-	20	400	2,80
HHOR46401T	4"	102,0	102,0	-	116,0	5	70	-	20	510	3,80

Tube: NBR, black, smooth, antistatic

Reinforcement: Textile wrapped, zinc plated double steel wire helix (ID >2.1/2" zinc plated steel wire helix)

Cover: SBR-EPDM, black, abrasion resistant, ozone resistant, cloth impression

Temperature range (medium): -40°C to 100°C