



METRIC FEMALE 24° FLARE HEAVY 45° ELBOW
FEMMINA 45° METRICA SV.24° PESANTE DKOS

IPQ50

Steel – Zinc Coating

part number codice	hose ID			thread A	DIN 24°	B		CH		H		cut-off=C	
	[in]	[mm]	size			[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]
IPQ500603S	3/16"	4,8	3	14X1.5	6S	0,12	3,0	0,67	17	0,63	16	1,65	42
IPQ500604S	1/4"	6,4	4	14X1.5	6S	0,16	4,0	0,67	17	0,75	19	1,77	45
IPQ500803S	3/16"	4,8	3	16X1.5	8S	0,12	3,0	0,75	19	0,63	16	1,65	42
IPQ500804S	1/4"	6,4	4	16X1.5	8S	0,16	4,0	0,75	19	0,75	19	1,77	45
IPQ500805S	5/16"	8,0	5	16X1.5	8S	0,22	5,5	0,75	19	0,75	19	1,77	45
IPQ500806S	3/8"	9,5	6	16X1.5	8S	0,28	7,0	0,75	19	0,79	20	1,89	48
IPQ501004S	1/4"	6,4	4	18X1.5	10S	0,16	4,0	0,87	22	0,75	19	1,77	45
IPQ501005S	5/16"	8,0	5	18X1.5	10S	0,22	5,5	0,87	22	0,75	19	1,77	45
IPQ501006S	3/8"	9,5	6	18X1.5	10S	0,28	7,0	0,87	22	0,79	20	1,89	48
IPQ501204S	1/4"	6,4	4	20X1.5	12S	0,16	4,0	0,94	24	0,71	18	1,77	45
IPQ501205S	5/16"	8,0	5	20X1.5	12S	0,22	5,5	0,94	24	0,71	18	1,77	45
IPQ501206S	3/8"	9,5	6	20X1.5	12S	0,28	7,0	0,94	24	0,83	21	1,89	48
IPQ501208S	1/2"	12,7	8	20X1.5	12S	0,35	9,0	0,94	24	0,87	22	2,13	54
IPQ501405S	5/16"	8,0	5	22X1.5	14S	0,22	5,5	0,87	27	0,79	20	1,77	45
IPQ501406S	3/8"	9,5	6	22X1.5	14S	0,28	7,0	0,87	27	0,83	21	1,89	48
IPQ501408S	1/2"	12,7	8	22X1.5	14S	0,35	9,0	0,87	27	0,90	23	2,13	54
IPQ501606S	3/8"	9,5	6	24X1.5	16S	0,28	7,0	1,18	30	0,83	21	1,89	48
IPQ501608S	1/2"	12,7	8	24X1.5	16S	0,35	9,0	1,18	30	0,90	23	2,13	54
IPQ501610S	5/8"	16,0	10	24X1.5	16S	0,47	12,0	1,18	30	0,98	25	2,16	55
IPQ502008S	1/2"	12,7	8	30X2	20S	0,35	9,0	1,42	36	0,98	25	2,13	54
IPQ502010S	5/8"	16,0	10	30X2	20S	0,47	12,0	1,42	36	1,02	26	2,16	55
IPQ502012S	3/4"	19,0	12	30X2	20S	0,59	15,0	1,42	36	1,26	32	2,79	71
IPQ502510S	5/8"	16,0	10	36X2	25S	0,47	12,0	1,81	46	1,10	28	2,16	55
IPQ502512S	3/4"	19,0	12	36X2	25S	0,59	15,0	1,81	46	1,34	34	2,79	71
IPQ502516S	1"	25,4	16	36X2	25S	0,79	20,0	1,81	46	1,46	37	3,46	88
IPQ503016S	1"	25,4	16	42X2	30S	0,79	20,0	1,97	50	1,54	39	3,46	88
IPQ503020S	1.1/4"	31,8	20	45X2	30S	0,99	25,0	1,97	50	1,89	48	4,33	110
IPQ503820S	1.1/4"	31,8	20	52X2	38S	0,99	25	2,36	60	2,05	52	4,33	110
IPQ503824S	1.1/2"	38,1	24	52X2	38S	1,26	32	2,36	60	2,32	59	5,67	144