



METRIC STANDPIPE 45° ELBOW – ONE PIECE
FEMMINA 45° TUBOLARE PEZZO UNICO

IPQ00

[BEL-BES 45° DIN 2353]

Steel – Zinc Coupling

part number codice	hose ID			Type Tipo	T (Pipe)		B		cut-off=C		drop H	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]
IPQ000603S	3/16"	4,8	3	L-S	0,24	6	0,12	3,0	1,62	41	0,79	20
IPQ000604S	1/4"	6,4	4	L-S	0,24	6	0,16	4,0	1,65	42	1,18	30
IPQ000804S	1/4"	6,4	4	L-S	0,32	8	0,16	4,0	1,62	41	1,14	29
IPQ001004S	1/4"	6,4	4	L-S	0,39	10	0,16	4,0	1,62	42	1,18	30
IPQ001204S	1/4"	6,4	4	L-S	0,47	12	0,16	4,0	1,65	42	1,18	30
IPQ001005S	5/16"	8,0	5	L-S	0,39	10	0,22	5,5	1,97	50	1,02	26
IPQ001205S	5/16"	8,0	5	L-S	0,47	12	0,22	5,5	2,09	53	1,02	26
IPQ001006S	3/8"	9,5	6	L-S	0,39	10	0,28	7,0	2,01	51	1,34	34
IPQ001206S	3/8"	9,5	6	L-S	0,47	12	0,28	7,0	2,13	54	1,34	34
IPQ001406S	3/8"	9,5	6	S	0,55	14	0,28	7,0	2,01	51	1,06	27
IPQ001506S	3/8"	9,5	6	L	0,59	15	0,28	7,0	2,17	55	1,10	28
IPQ001606S	3/8"	9,5	6	S	0,63	16	0,28	7,0	2,17	55	1,10	28
IPQ001806S	3/8"	9,5	6	L	0,71	18	0,28	7,0	2,32	59	1,22	31
IPQ001408S	1/2"	12,7	8	S	0,55	14	0,37	9,5	2,05	52	1,06	27
IPQ001508S	1/2"	12,7	8	L	0,59	15	0,37	9,5	2,21	56	1,10	28
IPQ001608S	1/2"	12,7	8	S	0,63	16	0,37	9,5	2,17	55	1,10	28
IPQ001808S	1/2"	12,7	8	L	0,71	18	0,37	9,5	2,32	59	1,22	31
IPQ001810S	5/8"	16,0	10	L	0,71	18	0,47	12,0	2,32	59	1,22	31
IPQ002010S	5/8"	16,0	10	S	0,79	20	0,47	12,0	2,56	65	1,30	33
IPQ002012S	3/4"	19,0	12	S	0,79	20	0,59	15,0	2,60	66	1,30	33
IPQ002212S	3/4"	19,0	12	L	0,87	22	0,59	15,0	2,64	67	1,38	35
IPQ002512S	3/4"	19,0	12	S	0,99	25	0,59	15,0	3,03	77	1,55	40
IPQ002812S	3/4"	19,0	12	L	1,10	28	0,59	15,0	3,62	92	1,50	38
IPQ002516S	1"	25,4	16	S	0,99	25	0,79	20,0	3,19	81	1,55	40
IPQ002816S	1"	25,4	16	L	1,10	28	0,79	20,0	3,62	92	1,50	38
IPQ003016S	1"	25,4	16	S	1,18	30	0,79	20,0	3,59	91	1,74	45
IPQ003516S	1"	25,4	16	L	1,38	35	0,79	20,0	3,82	97	1,81	46
IPQ003816S	1"	25,4	16	S	1,50	38	0,79	20,0	4,06	103	2,01	51
IPQ003020S	1.1/4"	31,8	20	S	1,18	30	1,02	26,0	3,59	91	1,74	45
IPQ003520S	1.1/4"	31,8	20	L	1,38	35	1,02	26,0	3,82	97	1,81	46
IPQ003820S	1.1/4"	31,8	20	S	1,50	38	1,02	26,0	4,06	103	2,01	51
IPQ003824S	1.1/2"	38,1	24	S	1,50	38	1,26	32,0	4,06	103	2,01	51
IPQ004224S	1.1/2"	38,1	24	L	1,65	42	1,26	32,0	4,45	113	3,62	92