



BSP FEMALE 60° FLARE 45° ELBOW WIRE NUT  
FEMMINA 45° BSP S.V.60° DADO SPINATO

IPQ10

Steel – Zinc Coating

part number codice	hose ID			thread A	B		CH		cut-off=C		drop H	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]
IPQ100403S	3/16"	4,8	3	1/4-19	0,12	3,0	0,75	19	1,65	42	0,63	16,0
IPQ100404S	1/4"	6,4	4	1/4-19	0,16	4,0	0,75	19	1,77	45	0,67	17,0
IPQ100405S	5/16"	8,0	5	1/4-19	0,22	5,5	0,75	19	1,77	45	0,75	19,0
IPQ100406S	3/8"	9,5	6	1/4-19	0,28	7,0	0,75	19	1,89	48	0,79	20,0
IPQ100604S	1/4"	6,4	4	3/8-19	0,16	4,0	0,87	22	1,77	45	0,67	17,0
IPQ100605S	5/16"	8,0	5	3/8-19	0,22	5,5	0,87	22	1,77	45	0,75	19,0
IPQ100606S	3/8"	9,5	6	3/8-19	0,28	7,0	0,87	22	1,89	48	0,79	20,0
IPQ100608S	1/2"	12,7	8	3/8-19	0,35	9,0	0,87	22	2,05	52	0,91	23,0
IPQ100806S	3/8"	9,5	6	1/2-14	0,28	7,0	1,06	27	2,05	52	0,87	22,0
IPQ100808S	1/2"	12,7	8	1/2-14	0,35	9,0	1,06	27	2,13	54	0,91	23,0
IPQ100810S	5/8"	16,0	10	1/2-14	0,47	12,0	1,06	27	2,16	55	0,91	23,0
IPQ101008S	1/2"	12,7	8	5/8-14	0,35	9,0	1,18	30	2,16	55	0,95	24,0
IPQ101010S	5/8"	16,0	10	5/8-14	0,47	12,0	1,18	30	2,16	55	0,99	25,0
IPQ101208S	1/2"	12,7	8	3/4-14	0,35	9,0	1,26	32	2,16	55	1,02	26,0
IPQ101210S	5/8"	16,0	10	3/4-14	0,47	12,0	1,26	32	2,76	70	1,10	28,0
IPQ101212S	3/4"	19,0	12	3/4-14	0,59	15,0	1,26	32	2,87	73	1,18	30,0
IPQ101612S	3/4"	19,0	12	1-11	0,59	15,0	1,50	38	3,07	78	1,42	36,0
IPQ101616S	1"	25,4	16	1-11	0,79	20,0	1,50	38	3,46	88	1,42	36,0
IPQ102016S	1"	25,4	16	1.1/4-11	0,79	20,0	1,97	50	3,86	98	1,73	44,0
IPQ102020S	1.1/4"	31,8	20	1.1/4-11	1,02	26,0	1,97	50	4,33	110	1,81	46,0
IPQ102420S	1.1/4"	31,8	20	1.1/2-11	1,02	26,0	2,17	55	4,45	113	1,89	48,0
IPQ102424S	1.1/2"	38,1	24	1.1/2-11	1,26	32,0	2,17	55	5,67	144	1,89	48,0
IPQ103224S	1.1/2"	38,1	24	2-11	1,26	32,0	2,76	70	5,83	148	1,89	48,0
IPQ103232S	2"	50,8	32	2-11	1,73	44,0	2,76	70	6,06	154	3,23	82,0
IPQ103832S	2"	50,8	32	2.1/2-11	1,73	44,0	3,35	85	6,14	156	3,31	84,0
IPQ103838S	2.1/2"	63,0	40	2.1/2-11	2,17	55,0	3,35	85	4,13	105	2,56	65,0