



JIC FEMALE 37° FLARE 45° ELBOW THRUST WIRE NUT
FEMMINA 45° JIC SV.37° DADO SPINATO

IPQ70

Steel – Zinc Coating

part number codice	hose ID			thread A	B		CH		H		cut-off=C	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]
IPQ700103S	3/16"	4,8	3	7/16 – 20	0,12	3,0	0,67	17	0,63	16	1,65	42
IPQ700104S	1/4"	6,4	4	7/16 – 20	0,16	4,0	0,67	17	0,63	16	1,77	45
IPQ700204S	1/4"	6,4	4	1/2 – 20	0,16	4,0	0,75	19	0,63	16	1,77	45
IPQ700304S	1/4"	6,4	4	9/16 – 18	0,16	4,0	0,75	19	0,63	16	1,77	45
IPQ700305S	5/16"	8,0	5	9/16 – 18	0,22	5,5	0,75	19	0,67	17	1,77	45
IPQ700306S	3/8"	9,5	6	9/16 – 18	0,28	7,0	0,75	19	0,79	20	1,89	48
IPQ700406S	3/8"	9,5	6	3/4 – 16	0,28	7,0	0,94	24	0,83	21	1,89	48
IPQ700408S	1/2"	12,7	8	3/4 – 16	0,35	9,0	0,94	24	0,90	23	2,13	54
IPQ700410S	5/8"	16,0	10	3/4 – 16	0,47	12,0	0,94	24	0,98	25	2,17	55
IPQ700506S	3/8"	9,5	6	7/8 – 14	0,28	7,0	0,87	27	0,90	23	2,01	51
IPQ700508S	1/2"	12,7	8	7/8 – 14	0,35	9,0	0,87	27	0,90	23	2,17	55
IPQ700510S	5/8"	16,0	10	7/8 – 14	0,47	12,0	0,87	27	0,90	23	2,17	55
IPQ700608S	1/2"	12,7	8	1"1/16 – 12	0,35	9,0	1,26	32	1,02	26	2,17	55
IPQ700610S	5/8"	16,0	10	1"1/16 – 12	0,47	12,0	1,26	32	0,98	28	2,76	70
IPQ700612S	3/4"	19,0	12	1"1/16 – 12	0,59	15,0	1,26	32	1,26	32	2,80	71
IPQ700812S	3/4"	19,0	12	1"5/16 – 12	0,59	15,0	1,50	38	1,42	36	3,07	78
IPQ700816S	1"	25,4	16	1"5/16 – 12	0,75	19,0	1,50	38	1,42	36	3,46	88
IPQ700920S	1.1/4"	31,8	20	1"5/8 – 12	0,98	25,0	1,97	50	1,81	46	4,33	110
IPQ701024S	1.1/2"	38,1	24	1"7/8 – 12	1,26	32,0	2,16	55	1,89	48	5,67	144
IPQ701132S	2"	50,8	32	2"1/2 – 12	1,73	44,0	2,76	70	2,56	65	6,06	154