



BSP M/F REDUCING PLUG  
TAPPO DI RIDUZIONE M/F BSP

**PRT10**

**Steel – Zinc Coating**

part number codice	thread F1	thread F2	L		CH		Max Pressure	
			[in]	[mm]	[in]	[mm]	[psi]	[bar]
PRT100402S	1/4"-19	1/8"-28	0,79	20,0	0,75	19	1450	100
PRT100602S	3/8"-19	1/8"-28	0,79	20,0	0,87	22	2538	175
PRT100604S	3/8"-19	1/4"-19	0,79	20,0	0,87	22	1450	100
PRT100804S	1/2"-14	1/4"-19	0,94	24,0	1,06	27	2538	175
PRT100806S	1/2"-14	3/8"-19	0,94	24,0	1,06	27	1450	100
PRT101204S	3/4"-14	1/4"-19	0,98	25,0	1,26	32	2538	175
PRT101206S	3/4"-14	3/8"-19	1,02	26,0	1,26	32	2538	175
PRT101208S	3/4"-14	1/2"-14	1,02	26,0	1,26	32	1450	100
PRT101608S	1"-11	1/2"-14	1,22	31,0	1,62	41	2175	150
PRT101612S	1"-11	3/4"-14	1,22	31,0	1,62	41	2175	150
PRT102008S	1.1/4"-11	1/2"-14	1,30	33,0	1,97	50	1813	125
PRT102012S	1.1/4"-11	3/4"-14	1,30	33,0	1,97	50	1813	125
PRT102016S	1.1/4"-11	1"-11	1,34	34,0	1,97	50	1813	125
PRT102412S	1.1/2"-11	3/4"-14	1,42	36,0	2,17	55	1813	125
PRT102416S	1.1/2"-11	1"-11	1,42	36,0	2,17	55	1813	125
PRT102420S	1.1/2"-11	1.1/4"-11	1,42	36,0	2,17	55	1813	125
PRT103216S	2"-11	1"-11	1,69	43,0	2,76	70	1813	125
PRT103220S	2"-11	1.1/4"-11	1,69	43,0	2,76	70	1450	100
PRT103224S	2"-11	1.1/2"-11	1,69	43,0	2,76	70	1450	100

\* In case of high mechanical stress use reducing extended / In caso di alte sollecitazioni meccaniche usare Riduzioni a Colonna