



BSP MALE/FIXED FEMALE REDUCING NIPLES  
 PROLUNGA DI RIDUZIONE M/F GAS-BSP

**PR110**

**Steel – Zinc Coating**

part number codice	thread F1	thread F2	L		H		CH		Max Pressure	
			[in]	[mm]	[in]	[mm]	[in]	[mm]	[psi]	[bar]
PR1100204S	1/8"-28	1/4"-19	1,18	30,0	0,79	20,0	0,87	22	4351	300
PR1100402S	1/4"-19	1/8"-28	1,22	31,0	0,87	22,0	0,87	22	4351	300
PR1100406S	1/4"-19	3/8"-19	1,26	32,0	0,79	20,0	0,87	22	4351	300
PR1100408S	1/4"-19	1/2"-14	1,42	36,0	0,98	25,0	1,06	27	4351	300
PR1100602S	3/8"-19	1/8"-28	1,18	30,0	0,79	20,0	0,87	22	3626	250
PR1100604S	3/8"-19	1/4"-19	1,30	33,0	0,79	20,0	0,87	22	3626	250
PR1100608S	3/8"-19	1/2"-14	1,50	38,0	0,98	25,0	1,06	27	3626	250
PR1100612S	3/8"-19	3/4"-14	1,73	44,0	1,22	31,0	1,26	32	3626	250
PR1100804S	1/2"-14	1/4"-19	1,42	36,0	0,83	21,0	1,06	27	2901	200
PR1100806S	1/2"-14	3/8"-19	1,42	36,0	0,83	21,0	1,06	27	2901	200
PR1100812S	1/2"-14	3/4"-14	1,81	46,0	1,22	31,0	1,26	32	2901	200
PR1100816S	1/2"-14	1"-11	1,85	47,0	1,26	32,0	1,62	41	2901	200
PR1101204S	3/4"-14	1/4"-19	1,57	40,0	0,91	23,0	1,26	32	2901	200
PR1101206S	3/4"-14	3/8"-19	1,65	42,0	0,98	25,0	1,26	32	2901	200
PR1101208S	3/4"-14	1/2"-14	1,65	42,0	0,98	25,0	1,26	32	2901	200
PR1101216S	3/4"-14	1"-11	1,97	50,0	1,30	33,0	1,62	41	2901	200
PR1101608S	1"-11	1/2"-14	1,97	50,0	1,22	31,0	1,62	41	2901	200
PR1101612S	1"-11	3/4"-14	1,97	50,0	1,22	31,0	1,62	41	2901	200
PR1101620S	1"-11	1.1/4"-11	2,05	52,0	1,30	33,0	1,97	50	2901	200
PR1102012S	1.1/4"-11	3/4"-14	2,11	53,5	1,26	32,0	1,97	50	2175	150
PR1102016S	1.1/4"-11	1"-11	2,00	51,0	1,18	30,0	1,97	50	2175	150
PR1102024S	1.1/4"-11	1.1/2"-11	2,00	51,0	1,18	30,0	2,17	55	2175	150
PR1102412S	1.1/2"-11	3/4"-14	2,16	55,0	1,30	33,0	2,17	55	2175	150
PR1102416S	1.1/2"-11	1"-11	2,16	55,0	1,30	33,0	2,17	55	2175	150
PR1102420S	1.1/2"-11	1.1/4"-11	2,16	55,0	1,30	33,0	2,17	55	2175	150
PR1102432S	1.1/2"-11	2"-11	2,56	65,0	1,69	43,0	2,76	70	2175	150
PR1103216S	2"-11	1"-11	2,68	68,0	1,69	43,0	2,76	70	2175	150
PR1103220S	2"-11	1.1/4"-11	2,68	68,0	1,69	43,0	2,76	70	2175	150
PR1103224S	2"-11	1.1/2"-11	2,68	68,0	1,69	43,0	2,76	70	2175	150