



ADAPTER F/F BSP 60° FLARE 45° WITH TRUST WIRE NUT
ADATTATORE BSP F/F GIREVOLE 45° SV.60° CON DADO SPINATO

A0710

Steel – Zinc Coating

| part number codice | thread F1 | thread F2 | L | | H | | CH1 | | CH2 | | Max Pressure | |
|-----------------------|--------------|--------------|------|-------|------|------|------|------|------|------|--------------|-------|
| | | | [in] | [mm] | [in] | [mm] | [in] | [mm] | [in] | [mm] | [psi] | [bar] |
| A07100404S | 1/4"-19 | 1/4"-19 | 2,30 | 58,5 | 0,71 | 18,0 | 0,75 | 19 | 0,75 | 19 | 5076 | 350 |
| A07100606S | 3/8"-19 | 3/8"-19 | 2,58 | 65,5 | 0,81 | 20,5 | 0,87 | 22 | 0,87 | 22 | 4351 | 300 |
| A07100808S | 1/2"-14 | 1/2"-14 | 2,72 | 69,0 | 0,98 | 25,0 | 1,06 | 27 | 1,06 | 27 | 3626 | 250 |
| A07101212S | 3/4"-14 | 3/4"-14 | 3,41 | 86,5 | 1,14 | 29,0 | 1,26 | 32 | 1,26 | 32 | 2901 | 200 |
| A07101616S | 1"-11 | 1"-11 | 3,94 | 100,0 | 1,48 | 37,5 | 1,50 | 38 | 1,50 | 38 | 2901 | 200 |
| A07102020S | 1.1/4"-11 | 1.1/4"-11 | 4,84 | 123,0 | 1,57 | 40,0 | 1,97 | 50 | 1,97 | 50 | 2538 | 175 |
| A07102424S | 1.1/2"-11 | 1.1/2"-11 | 6,22 | 158,0 | 1,89 | 48,0 | 2,17 | 55 | 2,17 | 55 | 2175 | 150 |
| A07103232S | 2"-11 | 2"-11 | 7,38 | 187,5 | 2,42 | 61,5 | 2,76 | 70 | 2,76 | 70 | 2175 | 150 |