



HYDRAULIC HOSE – TWO WIRE BRAID DIN EN 857 2SC  
TUBO 2SC – DIN EN 857

**HH2SC**

Part Number Codice	hose ID		Inside Ø [mm]	Braid Ø [mm]	Outside Ø [mm]	Working Pressure		Test Pressure Bar	Burst Pressure Bar	Bend Radius mm	Weight kg/m
	[in]	[mm]				Bar	Psi				
HH2SC0401T	1/4"	6,4	6,6	11,0	13,0	<b>400</b>	5800	800	1600	75	0,25
HH2SC0501T	5/16"	8,0	8,3	12,6	14,6	<b>350</b>	5075	700	1400	85	0,30
HH2SC0601T	3/8"	9,5	9,9	14,7	16,6	<b>330</b>	4785	660	1320	90	0,37
HH2SC0801T	1/2"	12,7	13,0	18,0	20,0	<b>275</b>	4000	550	1100	130	0,45
HH2SC1001T	5/8"	16,0	16,4	21,9	23,9	<b>250</b>	3625	500	1000	170	0,61
HH2SC1201T	3/4"	19,0	19,5	25,5	27,6	<b>215</b>	3120	430	860	200	0,76
HH2SC1601T	1"	25,4	26,0	32,9	35,6	<b>165</b>	2395	325	660	250	1,15

**Tube:** Synthetic rubber, resistant against hydraulic fluids

**Reinforcement:** Two braid of high tensile steel wire

**Cover:** Abrasion and ozone resistant synthetic rubber. Note: various covers available

**Temperature range (medium):** -40°C to 100°C (max 120°C intermittent)