



HYDRAULIC HOSE – SPECIAL WIRE BRAID
TUBO 2SN-K CON SPECIALE TRECCIA METALLICA

HH2SK

Part Number Codice	hose ID		Inside Ø [mm]	Braid Ø [mm]	Outside Ø [mm]	Working Pressure		Test Pressure Bar	Burst Pressure Bar	Bend Radius mm	Weight kg/m
	[in]	[mm]				Bar	Psi				
HH2SK0401T	1/4"	6,4	6,6	11,4	13,4	450	6525	900	1800	45	0,27
HH2SK0501T	5/16"	8,0	8,3	13	15,0	420	6090	840	1680	60	0,31
HH2SK0601T	3/8"	9,5	9,9	14,9	17,0	385	5585	770	1540	70	0,39
HH2SK0801T	1/2"	12,7	13,0	18,7	20,7	345	5000	690	1380	90	0,52
HH2SK1001T	5/8"	16,0	16,4	21,6	23,6	290	4205	580	1160	130	0,61
HH2SK1201T	3/4"	19,0	19,5	25,7	27,7	280	4060	560	1120	160	0,79
HH2SK1601T	1"	25,4	26,0	32,9	35,6	200	2900	400	800	210	1,15
HH2SK2001T	1.1/4"	31,8	32,5	40,5	43,5	175	2540	350	700	300	1,57

Tube: Synthetic rubber, resistant against hydraulic fluids

Reinforcement: Two braid of high tensile steel wire

Cover: Abrasion and ozone resistant synthetic rubber. Note: various covers available

Temperature range (medium): -40°C to 100°C (max 120°C intermittent)