



MULTISPIRAL HYDRAULIC HOSE – DIN EN 856 4SH

TUBO 4SH – DIN EN856 – 4 SPIRALI

HH4SH

Part Number Codice	hose ID		Inside Ø [mm]	Braid Ø [mm]	Outside Ø [mm]	Working Pressure		Test Pressure Bar	Burst Pressure Bar	Bend Radius mm	Weight kg/m
	[in]	[mm]				Bar	Psi				
HH4SH1201T	3/4"	19,0	19,5	28,3	31,9	420	6090	840	1680	280	1,43
HH4SH1601T	1"	25,4	26,0	35,4	38,7	380	5510	760	1520	340	2,20
HH4SH2001T	1.1/4"	31,8	32,5	42,3	45,2	350	5075	700	1380	460	2,58
HH4SH2401T	1.1/2"	38,1	38,7	49,2	53,4	290	4200	580	1160	560	3,30
HH4SH3201T	2"	50,8	51,1	63,2	67,3	250	3625	500	1000	700	4,94

Tube: Synthetic rubber, resistant against hydraulic fluids

Reinforcement: Four high tensile steel wire spiral layers

Cover: Abrasion and ozone resistant synthetic rubber – MSHA approved. Note: various covers available

Temperature range (medium): -40°C to 100°C (max 120°C intermittent)